

## UBERLUB GEAR OIL SERIES

**UBERLUB GEAR OIL SERIES** is a range of high-performance gear oils, formulated with high-quality mineral base oils, and an advanced multifunctional additive system to meet the requirements of API GL. Designed for the lubrication of hypoid gear sets in passenger vehicles, heavy duties and commercial vehicles, where they offer excellent extreme pressure (EP) and anti-wear properties.

### CHARACTERISTICS (TYPICAL VALUES)

UBERLUB GEAR OIL SERIES	75W-80	75W-90	80W-90	85W-140
Specific Gravity @ 15°C	0.865	0,889	0,889	0.90
Flash Point °C.	200	210	220	230
Viscosity cSt @ 100 °C	8,5	15.1	15,3	27,5
Viscosity cSt @ 40 °C	58	135	140	365
VI	119	114	112	101
Pour Point, °C.	-39	-36	-32	-30
Copper corrosion, 3 hours @ 121, ASTM D 130	1b	1b	1b	1b

The values given above are due to research and development studies.

There may be slight transitions from production to production properties.

#### Health, Safety and Environmental Information

The product is not expected to cause adverse effects on human health during the period of use in accordance with the instructions for use and the recommendations for forwarding the Safety Data Sheet (MSDS). It is recommended to use child protective equipment with constant consultation with the product. Used oils should not be consumed and poured into waste water channels. Used products T.C. It should be taken back or exceeded as specified in the Waste Oil Control Regulation of the Ministry of Environment and Forestry.

0264 275 8649

[www.uberlub.com.tr](http://www.uberlub.com.tr)

Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya

## UBERLUB GEAR OIL SERIES

### PROPERTIES AND PERFORMANCES

- Good anti-foaming properties ensure optimum oil film thickness, protecting components against wear, and minimise oil leakage.
- Good low-temperature fluidity ensures optimum lubrication, even in cold start-up conditions, and prevents start-up wear.
- Protection against corrosion and rusting extends equipment life, and reduces maintenance costs.
- Excellent thermal and oxidation stability minimise the build up of deposits and varnish, reducing wear, extending component life and ensuring longer oil life.

### INTERNATIONAL SPECIFICATIONS

**API**

GL-1, GL-2/3,  
GL-4, GL-5, MT-1

**MIL**

MIL-PRF-2105E



0264 275 8649



[www.uberlub.com.tr](http://www.uberlub.com.tr)



Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya